

LS25

SPECIFICATIONS

PA580-01-01B

ITEMS		MODEL	LS25-3.3	LS25-5	LS25-12	LS25-15	LS25-24	LS25-36	LS25-48
1	Nominal Output Voltage	V	3.3	5	12	15	24	36	48
2	Maximum Output Current	A	6	5	2.1	1.7	1.1	0.75	0.57
3	Maximum Output Power	W	19.8	25	25.2	25.5	26.4	27	27.36
4	Efficiency (Typ) (230VAC) (*1)	%	75	79	83	83	84	84	85
5	Input Voltage Range (*2)	-	88 ~ 264VAC (47-63Hz) or 125 ~ 373VDC (Withstand 300VAC Surge for 5 seconds)						
6	Input Current (Typ) (115/230VAC) (*1)	A				0.7 / 0.4			
7	Inrush Current (Typ) (*3)	-			30A at 230VAC, Ta=25°C (Cold Start)				
8	Harmonic Current	-			Built to meet IEC61000-3-2, -3				
9	Output Voltage Range	V	2.85 ~ 3.6	4.5 ~ 5.5	10.8 ~ 13.2	13.5 ~ 16.5	22 ~ 27.6	32 ~ 40	42 ~ 54
10	Ripple and Noise (*1, 4)	mV	80	80	120	120	120	150	200
11	Line Regulation (*5, 6)	mV	20	20	48	60	96	144	192
12	Load Regulation (*5, 7)	mV	40	40	96	120	192	288	384
13	Temperature Coefficient	-			Less than 0.02%/°C				
14	Over Current Protection (*8)	A			> 110% rated output current				
15	Over Voltage Protection (*9)	V			> 120% nominal output voltage				
16	Hold-Up Time (Typ) (115/230VAC) (*1)	ms			14 / 80				
17	Leakage current (*10)	-			< 1mA at 230VAC				
18	Series Operation	-			Possible				
19	Operating Temperature (*11)	-			- 25 ~ + 70 °C (Refer to Output Derating Curve)				
20	Operating Humidity	-			20 ~ 90%RH (No dewdrop)				
21	Storage Temperature	-			- 40 ~ +85°C				
22	Storage Humidity	-			10 ~ 95%RH (No dewdrop)				
23	Cooling	-			Convection cooling				
24	Withstand Voltage	-			Input - Output : 3.0kVAC (20mA), Input - FG : 1.5kVAC (20mA) Output - FG : 500VAC (100mA) for 1min.				
25	Isolation Resistance	-			Input - FG, Input - Output and Output - FG: More than 100MΩ (500VDC) at 25°C and 70%RH				
26	Vibration	-			At no operating, 10 - 55Hz (sweep for 1min) 19.6m/s² Constant, X, Y, Z 1hour each.				
27	Shock (In package)	-			Less than 196.1m/s²				
28	Safety	-			Approved by UL60950-1, IEC60950-1				
29	EMI	-			Built to meet EN55011/EN55022-B, FCC-B				
30	Immunity	-			Built to meet EN61000-4-2 (Level 2,3), -3 (Level 3), -4 (Level 3), -5 (Level 2,3), -6 (Level 3), -8 (Level 4), -11				
31	Weight (Typ)	g			170				
32	Dimension (L x W x H)	mm			79 x 51 x 28 (Refer to Outline Drawing)				

* Read instruction manual carefully , before using the power supply unit.

= NOTES=

* 1 : At Maximum Output Power, nominal input voltage, Ta = 25°C.

* 2 : For cases where conformance to various safety specs (UL, CSA) are required, to be described as 100 - 240VAC, 50 / 60Hz on name plate.

* 3 : Not applicable for the in-rush current to Noise Filter for less than 0.2mS.

* 4 : Ripple & noise are measured at 20MHz by using a 300mm twisted pair of load wires terminated with a 0.1uF film capacitor and a 47uF electrolytic capacitor.

* 5 : Measure line & load regulation at output terminal M3 tapped point.

* 6 : 88 - 264VAC, constant load.

* 7 : No load - Full load (Maximum power), constant input voltage.

* 8 : Current limit with automatic recovery.

Avoid to operate at overload or dead short for more than 30 seconds.

* 9 : Over voltage clamp by zener diode, hiccup mode.

* 10: Measured by each measuring method of UL (at 60Hz), Ta = 25°C.

* 11: Refer to Output Derating Curve (PA580-01-02_) for details of output derating versus ambient temperature.

* 12: All parameters NOT specifically mentioned are measured at 230VAC input, rated load and Ta = 25°C.

LS25

PA580-01-02

OUTPUT DERATING***COOLING : CONVECTION COOLING**

Ta (°C)	LOAD (%)	STANDARD MOUNTING
-25 ~ +40	100	
50	86.7(3.3V),100(OTHERS)	TB1
70	60	

OUTPUT DERATING CURVE